


# DALI Control Panel



## Product Features

- Colour touch screen (7").
- Background lighting with RGB LEDs.
- User-friendly application software.
- With DALI system functions of addressing and grouping.
- Ethernet CAT 5e RJ45 interface.
- Up-/downloading of the emergency lighting test report and firmware via Ethernet.
- Integral DALI power supplies on channel A and B.
- Internal power supply - connects directly to incoming supply.
- Function and endurance tests can be conducted in accordance with local regulations.
- Calendar-controlled function and duration test.
- Interconnection of multiple panels via cloud based solution for bigger installations.

Order Code	<b>VENT/DALI/CPS2</b>
DALI Interface	Wired DALI
Input voltage	100-240V 50/60Hz
Power consumption	12W
Degree of protection	IP20
Maximum Luminaire Connections	120 (60 per DALI Line)
Maximum DALI Cable Length	1.5mm <sup>2</sup> Cable - 300m 1mm <sup>2</sup> Cable - 200m
Cable entry	Rear Access
Mounting Options	Flush/ Semi- Recessed as Standard, Surface Mount -Optional (Back box ordered separately)
Cut-Out dimensions for Flush & Semi-Recessing options	205mm(W) X 118mm(H)
Incoming cable size cross sectional area mm <sup>2</sup>	1.5mm <sup>2</sup> to 2.5mm <sup>2</sup> single conductor
Strip length of mains wire conductor	5.0mm - 6.0mm
Protection class	Class II

## Materials

Housing: Polycarbonate  
Standard Colour: White - RAL 9016

## Warranty

Standard Warranty: 8 Years  
Alternative Warranty: 10 Years  
Add /10 Years to Order Code

System	Order Code	Power Consumption	Dimensions (mm)		
			A	B	C
DALI	VENT/DALI/CPS2	12W	155	235	41
Available Accessories					
Order Code	Description	Material	Dimensions(mm)		
VENT/DALI/BACKBOX	Surface Mounting Box	Polycarbonate	155	235	55

**PLEASE NOTE  
FOR REFERENCE PURPOSES ONLY**

Wiring Diagram – Self-Contained emergency operation

