

IP  
40

6Y  
Warranty

36m  
Viewing  
Distance

Wall  
Mounted

Class  
I

1.8 Kg

NiMh  
Battery

6500K

## Materials

Housing: Painted Steel  
Panel Legend: Polycarbonate

Standard Colour: White Ral 9016

Alternative Colour: Black - RAL 9017  
Add /BL to order code

## Warranty

Standard Warranty: 6 Years  
Alternative Warranty: 10 Years  
Add /10Y to order code

Order Code	EXM3/LED/**/DA
Mode of operation	Maintained DALI
Emergency duration	3 hours
Input voltage	230/240V (207Vac - 264Vac) 50/60Hz
Power consumption	7.2VA Irated = 30mA
Battery	Rechargeable Ni-Mh 3.6V, 2.1Ah
Battery low voltage cut off	3V
Battery discharge current @ 3.6Vdc	0.485A
Battery discharging limits	0.3-0.6A
Lamp	12x Samsung White LED
Lamp Life	L <sub>80 B50</sub> 80000 Hours
Nominal lamp current	Rated 0.35A CC
Nominal lamp power	P <sub>rated</sub> = 1W
Degree of protection	IP40 - for indoor use only.
Cable entry	Two 20mm conduit points on top of fitting, single 20mm conduit point on either side, and rear BESA terminal box mounting
Luminaire class	Class I
Weight	1.8kg
Packaging Weight	0.161kg
Standards	BS5266, EN62034, EN61347-2-7, EN61347-2-13, EN 60598-2-22
Environment	0°C to 45°C up to 80% relative humidity.

System	Order Code	Mode of Operation	Battery	Battery P/N	Lumens (Emergency)	Dimensions (mm)		
						A	B	C
DALI	EXM3/LED/**/DA	Maintained	3.6v 2.1Ah NiMh	70272	n/a	430	201	60
Alternative Systems Available:								
Standalone	EXM3/LED **	Maintained	4.8V 1.3Ah NiMh	70229	n/a	430	201	60
Central Battery	EX/LED/230S **	Slave	n/a	n/a	n/a	430	201	60
DALI Central Battery	ZEXLED230S**DA	Slave	n/a	n/a	n/a	430	201	60


## Alternative Legends



Replace \*\* with 01 for application of Left Arrow  
PN: 01710



Replace \*\* with 02 for application of Down Arrow  
PN: 01733



Replace \*\* with 03 for application of Right Arrow  
PN: 01754



Replace \*\* with 04 for application of Up Arrow  
PN: 01775