


EXLUX

IP67 Box Exit DALI Slave



Materials

Housing: Polycarbonate
Lid: Polycarbonate
Adhesive Legend: Polycarbonate
Gear-Tray: Painted Steel

Standard Colour: Grey Ral 7032

Warranty

Standard Warranty: 6 Years
Alternative Warranty: 10 Years
Add /10Y to order code

Order Code	ZEXLED230SIP**DA
Mode of Operation	Slave DALI
Input voltage	230/240V
Power consumption	7.2VA
Lamp	8 x High Powered White LEDs
Lamp Life	$L_{80} B_{50}$ 80000 Hours
Nominal lamp current	$I_{rated} = 0.35A$
Nominal lamp power	$P_{rated} = 1W$
Cable entry	To be Drilled and Glanded on installation (Glands not included)
Luminaire class	Class I
Weight	1.6kg
Packaging Weight	0.22kg
Standards	BS5266, EN62034, EN61347-2-7, EN61347-2-13, EN 60598-2-22
Environment	0°C to 55°C up to 80% relative humidity.

System	Order Code	Mode of Operation	Battery	Battery P/N	Viewing Distance	Dimensions (mm)		
						A	B	C
DALI Central Battery	ZEXLED230SIP**DA	Slave	n/a	n/a	32 Metres	379	189	132
Alternative Systems Available:								
Standalone	EXM3/LEDIP67/**	Maintained	4.8V 1.3Ah NiMh	70229	32 Metres	379	189	132
Central Battery	ZEXLED240SIP**	Slave	n/a	n/a	32 Metres	379	189	132
DALI	ZEXM3LIP67DAL**	Maintained	3.6V 4.5Ah NiMh	70151	32 Metres	379	189	132


Alternative Legends



Replace ** with 01 for application of Left Arrow
PN: 01970



Replace ** with 02 for application of Down Arrow
PN: 01971



Replace ** with 03 for application of Right Arrow
PN: 01972



Replace ** with 04 for application of Up Arrow
PN: 01973