



EXLUX PLUS

Box Exit Slave



IP 40	6Y Warranty	57m Viewing Distance	Wall Mounted
Class I	4 Kg	8W	6500K

Materials

Housing: Painted Sheet Steel
Panel Legend: Polycarbonate

Standard Colour: White Ral 9016

Alternative Colour: Others colours available upon request

Warranty

Standard Warranty: 6 Years
Alternative Warranty: 10 Years
Add /10Y to order code

Order Code	ZEXLED230SXL**
Mode of operation	Slave
Input voltage	230/240V (207Vac - 264Vac) 50/60Hz
Power consumption	15.5VA, $I_{nom} = 0.065A$
Lamp	2 X Osram LED strips
Lamp Life	$L_{80 B_{50}}$ 80000 Hours
Nominal lamp current	$I_{rated} = 0.35A$
Nominal lamp power	$P_{rated} = 8W (2x4W)$
Degree of protection	IP40
Cable entry	Two 20mm conduit points on top of fitting, Two 20mm conduit point on rear-BESA terminal box mounting
Luminaire class	Class I
Weight	4kg
Packaging Weight	0.25kg
Standards	BS5266, EN62034, EN61347-2-7, EN61347-2-13, EN 60598-2-22
Environment	0°C to 55°C up to 80% relative humidity.

System	Order Code	Mode of Operation	Battery	Battery P/N	Viewing Distance	Dimensions (mm)		
						A	B	C
Central Battery	ZEXLED230SXL**	Slave	n/a	n/a	57 Metres	730	300	164
Alternative Systems Available:								
Standalone	EXM3/LED/XL **	Maintained	4.8V 4.5Ah NiCd	70123	57 Metres	730	300	164
DALI	ZEXM3LEDXL**DA	Maintained	4.8V 4.5Ah NiCd	70240	57 Metres	730	300	164
DALI Central Battery	ZEXLED230SXL**DA	Slave Dali	n/a	n/a	57 Metres	730	300	164


Alternative Legends




Replace ** with 01 for
application of Left Arrow
PN: 01712



Replace ** with 02 for
application of Down Arrow
PN: 01735



Replace ** with 03 for
application of Right Arrow
PN: 01756



Replace ** with 04 for
application of Up Arrow
PN: 01777