



IP  
40

6Y  
Warranty

36m  
Viewing  
Distance

Ceiling  
Mounted



6500K

## Materials

Housing:	Painted Steel
Panel Legend:	Polycarbonate
Standard Colour:	White Ral 9016
Alternative Colour:	Black - RAL 9017 Add /BL to order code

## Warranty

Standard Warranty:	6 Years
Alternative Warranty:	10 Years Add /10Y to order code

Order Code	EX/LED/230S/2
Mode of operation	Slave
Input voltage	230/240V (207V AC - 264V AC) 50/60Hz
Power consumption	5VA, $I_{nom}$ = 0.025A
Lamp	2 x 8 String SM LED Strip
Lamp Life	$L_{80}$ $B_{50}$ 80000 Hours
Nominal lamp current	$I_{rated}$ = 0.35A
Nominal lamp power	$P_{rated}$ = 1W
Degree of protection	IP40 - for indoor use only.
Cable entry	Two 20mm conduit points on top of fitting.
Luminaire class	Class I
Weight	1.9kg
Packaging Weight	0.161kg
Standards	BS5266, EN62034, EN61347-2-7, EN61347-2-13, EN 60598-2-22
Environment	0°C to 55°C up to 80% relative humidity.

System	Order Code	Mode of Operation	Battery	Battery P/N	Viewing Distance	Dimensions (mm)		
						A	B	C
Central Battery	EX/LED/230S/2	Slave	n/a	n/a	36 Metres	430	200	102
Alternative Systems Available:								
Standalone	EXM3/LED/2	Maintained	4.8V 1.3Ah NiMh	70229	36 Metres	430	200	102

## Legends (Ordered Separately)



Left Arrow  
PN: 01710



Down Arrow  
PN: 01733



Right Arrow  
PN: 01754



Up Arrow  
PN: 01775