



EXLUX PLUS

Box Exit



IP 40	6Y Warranty	57m Viewing Distance	Wall Mounted
Class I	4.5 Kg	NiCd Battery	6500K

Materials

Housing: Powder Coated Sheet Steel
Panel Legend: Polycarbonate

Standard Colour: White Ral 9016

Alternative Colour: Others colours available upon request

Warranty

Standard Warranty: 6 Years
Alternative Warranty: 10 Years
Add /10Y to order code

Order Code	EXM3/LED/XL **
Mode of operation	Maintained
Emergency duration	3 hours
Input voltage	230/240V (207Vac - 264Vac) 50/60Hz
Power consumption	15.5VA, I _{nom} = 0.065A
Battery charger	Nominal charge 0.18A
Battery charging limits	100mA to 300mA - 4.0Vdc to 7.0Vdc
Battery low voltage cut off	4.0Vdc
Battery discharge current @ 4.8Vdc	1.2A
Battery discharging limits	up to 1.3A for 3 hours
Lamp	2 X Osram LED strips
Lamp Life	L _{80 B50} 80000 Hours
Nominal lamp current	I _{rated} = 0.35A
Nominal lamp power	P _{rated} = 8W (2x4W)
Degree of protection	IP40
Cable entry	Two 20mm conduit points on top of fitting, Two 20mm conduit point on rear-BESA terminal box mounting
Luminaire class	Class I
Weight	4.5kg
Packaging Weight	0.25kg
Standards	BS5266, EN62034, EN61347-2-7, EN61347-2-13, EN 60598-2-22
Environment	0°C to 45°C up to 80% relative humidity.

System	Order Code	Mode of Operation	Battery	Battery P/N	Viewing Distance	Dimensions (mm)		
						A	B	C
Standalone	EXM3/LED/XL **	Maintained	4.8V 4.5Ah NiCd	70123	57 Metres	730	300	164
Alternative Systems Available:								
Central Battery	ZEXLED230SXL**	Slave	n/a	n/a	57 Metres	730	300	164
DALI	ZEXM3LEDXL**DA	Maintained	4.8V 4.5Ah NiCd	70240	57 Metres	730	300	164


Alternative Legends



Replace ** with 01 for application of Left Arrow
PN: 01712



Replace ** with 02 for application of Down Arrow
PN: 01735



Replace ** with 03 for application of Right Arrow
PN: 01756



Replace ** with 04 for application of Up Arrow
PN: 01777