WTL 2X18W IP67 Emergency Twinspot







0

D



















Housing: Polycarbonate Standard Colour: Ivory RAL 1014

Warranty

Standard Warranty: 3 Years Alternative Warranty: 6 Years

Add /6Y to Order Code

Order Code	WTL2X18WLED/NM3				
Mode of operation	Non-maintained				
Input voltage	230/240V (207VAC - 264VAC) 50/60Hz				
Battery charger	Fully automatic, current limited constant voltage				
Lamp	2 x LED lamp heads total wattage 36 watts Each LED lamp contains 2 high power LEDs				
Lamp lumen level emergency	1085 lumens for each lamp head				
Battery	Rechargeable sealed lead acid battery 12V 7.0Ah				
Degree of protection	IP67				
Power consumption	20VA for 24 hours upon initial charge <9VA once charged				
Cable entry	To be Drilled and Glanded on installation (Glands not included)				
Emergency duration	3 hours				
Weight	8.6 kg				
Packaging Weight	0.235 kg				
Standards	EN 60598.2.22 EN61347-2-7 EN55015				
Environment	0°C to 30°C up to 80% relative humidity				

System Order Code	Order Code	Mode of Operation	Battery	Battery	Lumens	Dimensions (mm)				
			P/N	(Emergency)	Α	В	С	D		
Standalone	WTL2X18WLED/NM3	Non-Maintained	12V 7Ah SLA (Qty:2)	70162	2 x 1085	347	316	100	237	
Alternative Systems Available:										
Central Battery	ZWTL2X18WL230S	Slave	n/a	n/a	2 x 1085	347	316	100	237	