



Galaxy 2

Circular LED Dual DALI Emergency Bulkhead



2250
Mains
Lumens

630
Emergency
Lumens

**3000K/
4000K**

**Ceiling
and
Wall
Mounting**

LiFePO4
Battery

Homogeneous
Light Effect

IP
65

8Y
Warranty

Materials

Housing: Polycarbonate

Standard Colour: White - RAL 9003
Alternative Colours: Black - RAL 9005
Add /BL to Order Code

Alternative Colours Available Upon Request

Warranty


Standard Warranty: 8 Years
Alternative Warranty: 10 Years
Add /10 Years to Order Code

Order Code	GC2M3/LED/DADA
Mode of operation	Dual Mains & Maintained DALI
Emergency duration	3 Hour
Input voltage	220-240V 50/60Hz
Battery type	6.4V 6.4Ah LiFePO4
Battery low voltage cut off	5 VDC
Battery discharge current @ 6.4V DC	0.98A
Lamp	LED
Lamp colour	4000K (Selectable for 3000K)
Lamp lumen level in Mains	2250lm
Lamp Lifetime	L ₈₀ B ₅₀ 50000Hrs
MacAdam Ellipse/SDCM rating	<6
Lamp lumen level in emergency	630lm
Ingress Protection	IP65
Impact Resistance	IK10
Cable entry	20mm on sides and rear of product
Luminaire class	Class II
Product Weight	1.6Kg
Packaging Weight	0.2Kg
Standards	EN61347-2-7, EN61347-2-13, EN 60598-2-22, EN 55015
Environment	0°C to 40°C up to 80% relative humidity

System	Order Code	Mode of Operation	Battery	Battery P/N	Lumens (Mains)	Lumens (Emergency)	Dimensions (mm)	
							A	B
Dual DALI	GC2M3/LED/DADA	Dual Mains & Maintained DALI	6.4V 6.4Ah LiFePO4	70258	2250	630	352	67.5
Alternative Systems Available: Specification Sheets Available Upon Request								
DALI	GC2M3/LED/DA	Maintained	6.4V 6.4Ah LiFePO4	70258	2250	630	352	67.5
Standalone	GC2M3/LED	Maintained	6.4V 1.5Ah LiFePO4	70271	2250	200	352	67.5
Mains	GC2/LED/230	Mains	-	-	2250	-	352	67.5

Photometrics

Mounting Height	Lighting level directly under Luminaire (Lux)	Luminaire Spacing (Metres)			
		Escape Route		Open Plan	
		1.0lx	1.0lx	0.5lx	0.5lx
2m	12.16	4.4	10.7	4.3	11.0
2.5m	7.78	4.8	11.8	4.7	12.2
3m	5.40	5.1	12.7	5.0	13.2
4m	3.04	5.6	14.2	5.5	15.1
6m	1.35	6.0	16.0	6.2	18.0
8m	0.76	5.7	16.8	6.5	20.1
10m	0.49	4.7	16.8	6.4	21.7



www.ventilux.com ● sales@ventilux.ie ● sales@ventilux.co.uk (UK Enquiries Only) ● SS2-284-02

We adopt a policy of continuous product and services improvement and we reserve the right to vary details without prior notice
For Warranty Terms please visit the Ventilux website